

Boiler Lizard®, Patented

DESCRIPTION

Cortec's Boiler Lizard® contains Vapor phase Corrosion Inhibitor powder in a polyvinyl alcohol (PVA) water-soluble bag. The powder formulation is free of phosphates, heavy metals, nitrites, and free amines. Designed for dry lay-up of boilers, the Boiler Lizard® protects metals in enclosed spaces. The VpCIs vaporize and adsorb on the metal surfaces, reaching all recessed areas and interior cavities.

PACKAGING & STORAGE

Boiler Lizards are supplied in carton tubes (1 bag per tube).

Tube - 3" D x 37" H (8 cm x 94 cm)
Bag - 4" W x 34" H (10 cm x 86 cm).

To ensure best product performance, store in original packaging, indoors, and out of direct sunlight at 40-100 °F (4-38 °C).

Shelf life: 2 years

VpCI® ADDITIVES FOR WATER TREATMENT



FEATURES

- Multi-phase protection (vapor phase, liquid phase, and at the air-water interface)
- Easy and safe to handle
- Water-soluble, non-irritating PVA bags
- Formulation is free of phosphate, heavy metals, nitrites, and free amines

BENEFITS

- Provides continuous corrosion protection during dry lay-up period of up to 12 months
- Protects ferrous metals and aluminum
- Vapor phase corrosion inhibiting action protects inaccessible and recessed surfaces
- Requires little or no surface preparation for routine shutdown maintenance
- Protective layer does not need to be removed prior to equipment start-up
- Eliminates need for other forms of protection including nitrogen blankets, moisture-absorbing material (e.g., quicklime or silica gel desiccant), and dry air circulation
- Reduces chemical consumption and costs
- Increases worker productivity and safety
- Protects up to 1,000 gallon system capacity per bag (5 yd³ or 3.8 m³)

TYPICAL PROPERTIES

Appearance	White to off-white powder (inside water-soluble PVA bag)
pH	6-7 (1% aqueous)
Melting Point	371-398 °F (188-203 °C)

Boiler Lizard®, Patented

APPLICATION

Completely drain and cool boiler down. Remove from and discard outer protective bag. Place Boiler Lizard® flat in boiler and slit open the inner water-soluble bag to begin total corrosion protection. Slit this inner bag 2" (5 cm) from one end to 2" (5 cm) from the other end. Seal all openings to the boiler internals. No product or inner bag removal is required prior to boiler start-up. When the boiler is put back in service, fill with water and employ normal start-up procedure. The inner PVA bag will dissolve.

Precautions:

- Do not use on copper, copper-based alloys, and other soft yellow metals. Compatibility with non-metallics should be evaluated.
- Caking of powder may occur when it is exposed to moisture and then dried. The likelihood of this is increased when powder is exposed to high heat and multiple wet/dry cycles. When powder gets caked, baked, and hardened it requires removal by mechanical means or by aggressive acid clean.



LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec® Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec® Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec® Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec® Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec® Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec® Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC® CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.