

VpCI®-429, Patent Pending



Panel cleaned with VpCI-429
and then coated with VpCI-386 Clear

PRODUCT DESCRIPTION

VpCI-429 is a very effective rust remover and cleaner for different metals. The chemistry of this product is based on the chelating abilities of its ingredients.

VpCI-429 not only completely cleans rusted surfaces, but also prevents further rusting during the cleaning process. After cleaning, there is no need for neutralization or additional rust preventative materials.

VpCI-429 is environmentally and user friendly, has a neutral pH, is made of biodegradable and renewable materials, is non-irritative, and not harmful.

Metal surfaces treated with VpCI-429 can be painted without any problems; eliminating the step of additional preparation. In most cases, VpCI-429 acts as an adhesion promoter for coatings.

FEATURES

- Effectively removes rust and cleans the surface.
- Neutral pH and non-irritative.
- Provides protection to cleaned surfaces up to 4 weeks.
- Promotes adhesion of paint to cleaned surfaces.
- Made with biodegradable materials.
- Doesn't contain EDTA.
- Non-toxic, non-harmful.
- Works as a biocide potentiator (increases efficiency of biocides).



Panel cleaned with VpCI-429
and then coated with VpCI-386 Yellow

APPLICATION

Rust Removal

VpCI-429 is used in dip applications.

Step 1: Pour into asufficient amount into a container to completely cover the rusted metal.

Step 2: Leave the metal in the solution for 15-30 minutes (light rust) or overnight (very heavy rust).

Step 3: Rinse treated metal with water.
If some rust still remains on the surface, repeat step 2.

Step 4: After rinsing, dip the metal into a clean solution of VpCI-429 and allow to air dry. This will prevent rust up to 4-5 weeks.

Salt Removal

VpCI-429 is economical and very effective in removing marine and deicing salts from machinery and other equipment. For the best performance in that application, use at 0.2-0.7% by weight at ambient temperatures.

PHYSICAL PROPERTIES

Appearance	Clear liquid
Non-volatile Content	5-6
Odor	Light
pH	6.5-7.0
Weight per Gallon	8.4-8.6 lb/gal. (1.01–1.03 kg/l)

PACKAGING AND STORAGE

VpCI-429 is available in 5 gallon (19 liter), 55 gallon (208 liter) drums, totes, and bulk. Store product in a heated warehouse to avoid freezing.

Minimum storage temperature: 32°F (0°C)

Maximum storage temperature: 120°F (49°C)

Toxicological Testing Results

Species	NOEC/LOEC, ppm	48-hr LC50* ppm
D.pulex	5000/>5000	>5000
P. promelas	5000/>5000	>5000

*LC50/EC50-50% of Lethal concentration/50% of Effective Concentration respectively.

FOR INDUSTRIAL USE ONLY

KEEP OUT OF REACH OF CHILDREN

NOT FOR INTERNAL CONSUMPTION

CONSULT SAFETY DATA SHEET FOR MORE

INFORMATION

LIMITED WARRANTY

All statements, technical information and recommendations contained herein are based on tests Cortec Corporation believes to be reliable, but the accuracy or completeness thereof is not guaranteed.

Cortec Corporation warrants Cortec® products will be free from defects when shipped to customer. Cortec Corporation's obligation under this warranty shall be limited to replacement of product that proves to be defective. To obtain replacement product under this warranty, the customer must notify Cortec Corporation of the claimed defect within six months after shipment of product to customer. All freight charges for replacement products shall be paid by customer.

Cortec Corporation shall have no liability for any injury, loss or damage arising out of the use of or the inability to use the products.

BEFORE USING, USER SHALL DETERMINE THE SUITABILITY OF THE PRODUCT FOR ITS INTENDED USE, AND USER ASSUMES ALL RISK AND LIABILITY WHATSOEVER IN CONNECTION THEREWITH. No representation or recommendation not contained herein shall have any force or effect unless in a written document signed by an officer of Cortec Corporation.

THE FOREGOING WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES, EXPRESS, IMPLIED OR STATUTORY, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTY OF MERCHANTABILITY OR OF FITNESS FOR A PARTICULAR PURPOSE. IN NO CASE SHALL CORTEC CORPORATION BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.



Distributed by:



printed on recycled paper  100% post consumer
Revised: 9/27/13. Cortec Corporation 2007-2013. Supersedes: 3/27/13.

Cortec® is a trademark of Cortec Corporation. © 2013, Cortec Corporation. All Rights Reserved.
Copying of these materials in any form without the written authorization of Cortec Corporation is strictly prohibited. ISO accreditation applies to Cortec's processes only.

www.esvasolutions.com